RMI Examples

To import the examples:

Download zip file to your computer
I. Dedipse select File > Import > General > Existing Projects into Workspace
Press next
Select archive file: (path to the downloaded .zip file)
Select archive file: (path to the downloaded .zip file)
Serves next
Tor un the GameClient as well as the GameServer you need to add some arguments to the eclipse run configuration as shown in the two screenshots below
Start the GameClient (SopraRmiClient/client/GameServer.java)



	000	Java – SopraRmiS	erver/src/client/GameClient.java – Eclipse – /Users/knab/Documents/workspace
	Ё• 🗒 奋 〕 糁• ❶• • 〕 總 部 @• 〕 總 奋 ⋪• 〕 ⅌ ⊿ ☜ 圓 面 〕 处 • ∛ + や や• ⇔•		
1	😫 Package Expl 🕱 🍃 Hierarchy 🗖 🗖	🕖 GameClient.java 🛿	
	E 🔩 🐨 🏹	package client;	
	Circles SopraRmiClient	000	Run Configurations
	▼ [™] src	Create, manage, and run con	figurations
	V 🖶 client	Run a Java application	
	GameClient.java		
	► trules	P B ¥ D 3.	
2	▶ 🔠 server		Name: GameClient
8	All System Library [JVM 1.6.0 (MacO!)		🕒 Main 🕪 Arguments 🔜 JRE 🍫 Classpath 🦆 Source 🐻 Environment 🔲 Common
	SopraRmiServer	Java Applet	Program arguments:
	▼ ∰ src	GameClient	
2	🕨 🔠 client	GameServer	
ė.	▶ tures	Ju JUnit	
	▶ J Game.java	Ju lask Context Test	
1	▶ 🕖 GameServer.java		
	IGame.java		
-	JRE System Library [JVM 1.6.0 (MacO)]		
	server.policy		
			Variables
			VM arguments:
			-Djava.rmi.server.hostname=localhost
\$			-Djava.rmi.server.codebase=file:/\$[project_loc]/bin/ -Djava.security.policy=client.policy
			bjevelseen exponey element of the second s
s,			
atri			
-p (
op			
tiv			Variables
T		6	Working directory
			Default: S(workspace loc:SonraRmiClient)
			O Other:
		5	
			Workspace) (File System) (Variables)